

Eaton EP-502636

Eaton xPole SPHT surge protection device, Combined arrester, transient voltage surge suppression T1&T2, AX



General specifications

PRODUCT NAME	Eaton xPole SPHT surge protection device
CATALOG NUMBER	EP-502636
EAN	9010653085270
PRODUCT LENGTH/DEPTH	105 mm
PRODUCT HEIGHT	86 mm
PRODUCT WIDTH	54 mm
PRODUCT WEIGHT	0.508 kg
CERTIFICATIONS	CE
MODEL CODE	SPHT12-275/3-AX

Technické údaje – elektrické

CONTINUOUS VOLTAGE
AT AC - MAX 275 V

CONTINUOUS VOLTAGE
AT DC - MAX 0 V

FOLLOW CURRENT
EXTINGUISHING
CAPABILITY 50 kA

NOMINAL VOLTAGE AT
AC 240 V

NOMINAL VOLTAGE AT
DC 0 V

SIGNALLING AT THE
DEVICE Optic

SPECIFIC ENERGY (W/R) 0 kJ/Ohm

VOLTAGE PROTECTION
LEVEL 1.5 kV

NOMINAL DISCHARGE
SURGE CURRENT (8/20) 25 kA

LIGHTNING IMPULSE
CURRENT (10/350 MS) 25 kA

Další informace

FEATURES Category type 1

FITTED WITH: Remote signaling contact

SYSTEM
CONFIGURATION TYPE TN-C

Technické údaje – mechanické

FRAME 3 modular spacing

MOUNTING METHOD DIN rail (top hat rail) 35 mm

DEGREE OF PROTECTION IP20

CONDUCTOR CROSS
SECTION (FLEXIBLE, FINE-
STRAND) - MAX 25 mm²

CONDUCTOR CROSS
SECTION (SOLID, SOLID-
STRAND) - MAX 35 mm²

NUMBER OF
CONDUCTORS WITHOUT
EARTHING 3

Zdroje

INSTALAČNÍ NÁVODY [eaton-xpole-spht-surge-protection-device-il235010zu.pdf](#)

NÁZEV PROJEKTU:

ČÍSLO PROJEKTU:

PŘIPRAVIL:

DATUM:



Eaton Corporation Plc. Eaton House
30 Pembroke Road
Dublin 4, Irsko
Eaton.com

© 2025 Eaton. Všechna práva vyhrazena.

Sledujte nás na sociálních sítích,
abyste získali nejnovější informace o
produktech a podpoře.

