

ETITEC M T2 PV 1500/20 Y



Specifikace

Kód ETI	002440517
Popis	ETITEC M T2 PV 1500/20 Y
Počet modulů	3
Up - Úroveň ochrany napětí (kV)	5kV
Typ proudu	DC
Montáž	PV ochrana
Funkce	SPD
Použití (IEC/VDE)	II / C
Počet pólů	2
Stupeň krytí IP	IP20
Typ	T2
Dálková signalizace	Ne
DC max continous operating voltage Uc	1500V
Vestavná hloubka (mm)	70mm
Aplikovaná technologie	MOV
Svodový proud	Ano
In (8/20)	20kA
Skupina katalogu	ETITEC M PV

[Online stránka produktu](#)

Další dokumentace

[Katalog technických údajů](#)[3D model](#)[2D File](#)[Návod](#)[Prohlášení CE](#)[Eplan file](#)

Mezinárodní klasifikace ETIM

Klasifikace	EC000941
Název třídy	Surge protection device for power supply systems
System configuration DC	1
System configuration IT	
System configuration TN	
System configuration TN-C	
System configuration TN-C-S	
System configuration TN-S	
System configuration TT	
System configuration other	
Number of conductors (without earthing)	2
Nominal discharge surge current (8/20)	20
Short-circuit breaking capacity (I _{sc})	11
Max. discharge surge current (8/20)	30
Max. continuous voltage DC	1500
Mounting method	DIN rail (top hat rail) 35 mm
Construction size	3 modular spacing
Max. PV-voltage	1250
Voltage protection level	5
Max. conductor cross section solid (solid, stranded)	35
Max. conductor cross section flexible (fine-strand)	25
With remote signalling contact	
Integrated backup fuse	
Signalling at the device	Optical
Category type 2	1
Degree of protection (IP)	IP20