



E3ZM-B66

Photoelectric sensor, rectangular housing, stainless steel, red LED, retro-reflective, transparent object, 500 mm, with teach-button, NPN, Light-ON/Dark-ON, M8 4-pin connector

Shape	Cuboid
Sensing method	Retro-reflective
Sensing distance	500 mm
Sensing distance (min.)	100 mm
Setting method	Teach-In
Connection method	Connector M8 - 4 pin
Output type	NPN
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	Stainless steel
Thread size	Other
Product Width (unpacked)	10.8 mm
Product Height (unpacked)	31 mm
Product Depth (unpacked)	21 mm
Type of light	Polarized red light
Power supply voltage	10-30 V
Features	M.S.R., Transparent detection (PET bottle and tray)
Degree of protection (IP)	IP67/IP69K

	E39-L150	Sensor mounting Bracket for E3Z, 100mm high post
	E39-L151	Sensor mounting Bracket, for E3Z, 200mm high post
	E39-L203	Rear mounting bracket for E3AS-F/L models
	E39-L211	L-shaped mounting bracket for E3AS-F/L models
	E39-L212	Horizontal protective cover bracket for E3AS-F/L cable and pigtail models
	E39-L214	Protective metal cover for E3AS, horizontal surface mounting
	E39-L44	Mounting bracket for E3Z sensor, rear mounting
	E39-RP1	Reflector, polarizing, to use with E3ZM-B, 44mm x 64mm



Konektory a kabely s konektory M8

Průmyslové konektory
a kabely s konektory pro
jakékoli použití

Stahování dokumentace

CAD knihovny



E3Z Brožura

EN PDF 1,3 MB



E3ZM-B Series Katalogový list

EN PDF 2,9 MB



EAC Mark removal Upozornění na ukončení výroby

EN PDF 220,8 KB