

Part number

CX 06 CF



female modular insert, Mixo series, crimp connection, 6 poles, 1 module, 16 A 500 V 6 kV 3

Product description

Product type	modular insert
Series	Mixo
Connection type	crimp connection
Gender	female
N. of poles	6 poles
Size	1 module

Technical data

Current	16 A
Voltage	500 V
Rated impulse withstand voltage	6 kV
Pollution degree	3
Rated voltage according to UL/CSA	600 V
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure

Further technical details

Characteristics according to EN 61984	16A 400V 6kV 3; 16A 400/690V 6kV 2
Insulation resistance	≥ 10 GΩ
Weight	9,70 g
Operating temperature range (min, max)	-40°C ... +125°C
UL 94 flammability rating	V-0

Material properties

Main material	polycarbonate
Colour	RAL 7032 grey

Approvals / Standards

Reference standard	EN 61984:2009-06
---------------------------	------------------

General ordering information

EAN13 code	8015747041881
-------------------	---------------

Packaging Information

Packaging length	180,00 mm
Packaging height	130,00 mm
Packaging width	150,00 mm
Packaging weight	0,80 kg
Packaging volume	3,51 dm ³
Packaging description	Carton box
Packaging quantity	60 Pcs
Packaging EAN code	8015747221276
Sub-packaging length	35,00 mm
Sub-packaging height	40,00 mm
Sub-packaging width	155,00 mm
Sub-packaging weight	0,13 kg
Sub-packaging volume	0,22 dm ³
Sub-packaging description	Carton tray
Sub-packaging quantity	10 Pcs
Sub-packaging EAN barcode	8015747041898


Part number

CX 06 CF




Catalogue drawings


CX 06 CM



CX 06 CF



Catalogue drawings



Notes