

ETIMAT 10 3p C80



Specifikace

Kód ETI	002135731
Popis	ETIMAT 10 3p C80
Jmenovitý proud (A)	80A
Vypínací charakteristika	C
Počet pólů	3
Zkratová odolnost (kA)	20kA
Typ napětí	AC
Jmenovité impulsní výdržné napětí (kV)	4kV
Jmenovité AC napětí (V)	415V
Jmenovité DC napětí (V)	415V
Jmenovitá frekvence (Hz)	50Hz/60Hz
Jmenovitý průřez (mm ²)	25mm ² -50mm ²
Normy	IEC/EN 60898-1, IEC 60947-2
Funkce	MCB

[Online stránka produktu](#)

Další dokumentace

[Katalog technických údajů](#)[3D model](#)[2D File](#)[Prohlášení CE](#)[Eplan file](#)

Mezinárodní klasifikace ETIM

Klasifikace	EC000042
Název třídy	Miniature circuit breaker (MCB)
Release characteristic	C
Number of poles (total)	3
Number of protected poles	3
Rated current	80A
Rated voltage	415V
Rated insulation voltage U_i	440V
Rated impulse withstand voltage U_{imp}	4kV
Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V	20kA
Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V	20kA
Voltage type	Other
Frequency	50...60Hz
Current limiting class	3
Over voltage category	3
Pollution degree	3
Additional equipment possible	1
Width in number of modular spacings	4,5
Built-in depth	75mm
Degree of protection (IP)	IP20
Ambient temperature during operating	-25...55°C
Connectable conductor cross section multi-wired	2.5...50mm ²
Connectable conductor cross section solid-core	2.5...50mm ²