


Sensor-switched LED floodlight

Spot ONE

Sensor

EAN 4007841 058616

Article number 058616



Wall embellishment in top form. Swivelling sensor-switched LED wall spot ONE Sensor in a clean-cut design and with a light output of 520 lm from 7 W. 90° infrared motion detector with up to 10 m reach. Selectable time and twilight threshold. Several spots can be interconnected by cable. Includes replaceable GU-10 LED lamp.

Technical specifications

Dimensions (L x W x H)	175 x 97 x 98 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Mounting height max.	2,50 m
Sensor Technology	passive infrared
Output	7 W
Power consumption	0,5 W
Interconnection	Yes
Slave mode/selectable	No
Luminous flux	520 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Farbwiedergabeindex	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
With motion detector	Yes
Detection angle	90 °
Angle of aperture	90 °
Sneak-by guard	No
Reach, radial	r = 2 m (3 m ²)
Reach, tangential	r = 10 m (79 m ²)

Photo-cell controller	Yes
Twilight setting	2 – 1000 lx
Time setting	8 s – 35 Min.
Basic light level function	No
Main light adjustable	No
Settings via	Potentiometers
Soft light start	No
Continuous light	selectable
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
Includes corner wall mount	No
PU1, net weight	0,475 kg
Version	Sensor
PU1, EAN	4007841058616

Sensor-switched LED floodlight

Spot ONE


Sensor

EAN 4007841 058616

Article number 058616



Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,50 m

Orange: radial

Schwarz: tangential

Dimension Drawing

