

RBS220-1C-230V AC



Specifikace

Kód ETI	002464109
Popis	RBS220-1C-230V AC
Max. number of impulses per minute	20
Storage temperature (°C)	-30°C-80°C
Max. back-up fuse for short circuit protection	20A
Min. impulse duration between two impulses (ms)	150ms
Max. impulse duration at Uc (ms)	1h
Min. impulse duration at Uc (ms)	50ms
Distance between contacts and coil (mm)	6mm
Min. distance of open contacts (mm)	3mm
Počet modulů	1
Max. shock resistance (g)	15g
Resistance to humidity	95% RH
Funkce	Bistabilní spínač RBS
Napájecí napětí (V)	230V
Proud Ie AC1 (A)	20A
Typ napětí	AC
Počet přepínacích kontaktů	1
Jmenovitá frekvence (Hz)	50Hz/60Hz
Jmenovitý proud (A)	20A
Počet pólů	1
Terminal screw	M4 (main circuit)/M3 (control circuit)
Jmenovitý průřez (mm ²)	110mm ²
Tightening torque (Nm)	1.2Nm
Stupeň krytí IP	IP20
Okolní teplota (°C)	-25°C/55°C
Typ uchycení	TH 35
Jmenovité pracovní napětí (V AC)	440V
Jmenovité izolační napětí (V)	440V
Tepelný proud Ith (A)	20A
Šířka (mm)	17.5mm
Ztrátový výkon (W)	3W
Electrical cycles	10000
Mechanical cycles	100000
Normy	IEC/EN 60669-2-2

[Online stránka produktu](#)

Další dokumentace

[Katalog technických údajů](#)[3D model](#)[2D File](#)

Mezinárodní klasifikace ETIM

Klasifikace	EC000188
Název třídy	Latching relay
Function	Other
Mounting method	DIN rail
Width in number of modular spacings	1
Built-in depth	60mm
Number of contacts as normally open contact	1
Number of contacts as normally closed contact	1
Number of contacts as change-over contact	2
Control voltage 1	207...253V
Type of control voltage 1	AC
Frequency control voltage 1	50...60Hz
Rated switch current	20A
Supply voltage	440...440V
Voltage type (supply voltage)	AC
Manual operation possible	1

Rozměrový výkres

