

EU-Konformitätserklärung

EU Declaration of Conformity

Nr. / No. 097009651_02



Hersteller / Manufacturer:

Phoenix Contact GmbH & Co. KG

Anschrift / Address:

Flachsmarktstraße 8, 32825 Blomberg, Germany

Produktbezeichnung / Product designation:

SACC - (A)(B)(C)(D)(E)(F)(G)(H)

Die alleinige Verantwortung für die Ausstellung dieser Konformitätserklärung trägt der Hersteller. Die in dieser Erklärung bezeichneten Produkte stimmen mit den einschlägigen Anforderungen der folgenden Harmonisierungsrechtsvorschriften überein:

This declaration of conformity is issued under the sole responsibility of the manufacturer. The products specified in this declaration are in conformity with the following relevant harmonization legislation:

2014/35/EU

(OJ L 96, 29 March 2014)

Niederspannungs-Richtlinie

Low Voltage Directive (LVD)

Für die Beurteilung der Übereinstimmung wurden folgende einschlägige Normen herangezogen:

The following pertinent standards have been applied for the assessment of conformity:

EN 61076-2-101:2012

EN 61984:2009

Der folgende Anhang zu dieser EU-Konformitätserklärung ist integrativer Bestandteil dieser Erklärung.

The following annex to this EU declaration of conformity is an integral part of this declaration.

Blomberg, 2026-05-28

i.A.

Markus Amende
Business Unit Field Connectivity
Technology & Quality Services FCO

Ansprechpartner / Contact person

ppa.

Frank Mellies
Business Unit Field Connectivity
Vice President

Zeichnungsberechtigter / Authorized signatory

Nomenclature SACC QUICKON articles, CE based on LVD

Typenschlüssel

SACC - (A)(B)(C)(D)(E)(F)(G)(H)

Example:

(A)				-	(B)			(C)	(D)	-	(E)	(F)		-	(G)				-	(H)		
S	A	C	C	-	M	1	2	M	S	-	4	Q	O	-	0	,	3	4	-	M		

A - Product family

SACC	=	Sensor Actuator Connector for assembly
SACC-EE	=	Sensor Actuator Connector for assembly Essential Edition

B - Interface design

M12	=	Metric M12-Thread (M12x1)
blank	=	Metric M12-SPEEDCON Thread (M12x1)

C - Connector design

MS	=	Male straight
MR	=	Male angled
FS	=	Female straight
FR	=	Female angled

D - Mating face coding

blank	=	A-coded
B		B-coded
D	=	D-coded

E - number of poles

3	=	3-poles
4	=	4-poles

F - connection technology

QO	=	Insulation displacement connection (IDC) - QUICKON
----	---	--

G - cross wire-section

0,34	=	cross wire-section 0,14 mm ² ... 0,34 mm ²
0,50	=	cross wire-section 0,14 mm ² ... 0,50 mm ²
0,75	=	cross wire-section 0,34 mm ² ... 0,75 mm ²

H - Optional information

blank	=	plastic thread
M	=	metal thread
SCO	=	SPEEDCON fast locking
VA	=	stainless steel thread
XXXXX	=	All article designations may be followed by additional suffixes (any combination of letters, symbols and/or numbers) designating non-electrical variations such as color (e.g. BK= black), customer identification, packaging or plating options. Except: SH= shielded is not allowed