

SPMP



LED

220
240 V
50-60 Hz

SDCM
3

DIMM



IP
20

CRI
80

MULTI


EN
62 471
RG 0

80 000
L80B50


η_{ef} (lm/W)
95-115



SPMP190



SPMP KN



SPMP KO

Přisazená kruhová svítidla

Těleso:

Bíle lakovaný (RAL 9003) ocelový plech

Optický systém:

Světlovodivá akrylátová deska

KN - mikroprizmatický kryt

KO - opálový kryt

SPMP	W	lm		C	Ø	X	Y	kg
		KO	KN					
SPMP1000 190	9	970	1 050	56	184	120	140	0,9
SPMP1500 190	13	1 350	1 450					
SPMP2000 190	19	1 800	1 950					
SPMP3000 370	26	2 800	3 000		365	200	230	2,0
SPMP3000 370 MULTI	20 - 29	2100 - 3100	2 200 - 3 200					
SPMP4000 370	34	3 550	3 800					
SPMP4000 550	34	3 650	3 800		548	400	400	3,0
SPMP5000 550	40	4 100	4 500					

lm - světelný výkon svítidla

2200	2700	3000	4000	5700	6500	MIX	RGB	
×	○	○	●	○	×	×	×	×
ON OFF	1-10V	DALI	Bluetooth					
●	×	○	○	×	×	×	×	×

● standard

○ volitelné

× nelze



PROFIL SVÍTIDLA



MONTÁŽNÍ DESKA



DETAIL KRYTU

