

Ordering information


Plastic enclosed DC switch-disconnectors




OTDCP_SA_




OTDCP_S_



OTDCP_11_



OTDCP_12_



OTDCP_22_

Plastic enclosed DC switch-disconnectors OTDCP_

M20 threaded knock-outs, compression glands have to be ordered separately. M16 threaded knock-outs available on request.

Number of poles	Rated operat. current [A] DC 21B 660 V / 1000 V	Type	Order number	Weight/unit [kg]
Up to 660 VDC				
Includes selector type red-yellow handle (I-O and ON-OFF indication)				
2	16 / 10	OTDCP16SA11M	1SCA125126R1001	0.55
2	25 / 16	OTDCP25SA11M	1SCA125127R1001	0.55
2	32 / 20	OTDCP32SA11M	1SCA125128R1001	0.55
Includes selector type black handle (I-O and ON-OFF indication)				
2	16 / 10	OTDCP16S11M	1SCA125129R1001	0.55
2	25 / 16	OTDCP25S11M	1SCA125130R1001	0.55
2	32 / 20	OTDCP32S11M	1SCA125131R1001	0.55

Number of poles	Rated operat. current [A] DC 21B 1000 V	Type	Order number	Weight/unit [kg]
Up to 1000 VDC				
Includes selector type red-yellow handle (I-O and ON-OFF indication)				
3	16	OTDCP16SA12M	1SCA125150R1001	0.59
3	25	OTDCP25SA12M	1SCA125151R1001	0.59
3	32	OTDCP32SA12M	1SCA125152R1001	0.59
Includes selector type black handle (I-O and ON-OFF indication)				
3	16	OTDCP16S12M	1SCA125153R1001	0.59
3	25	OTDCP25S12M	1SCA125154R1001	0.59
3	32	OTDCP32S12M	1SCA125155R1001	0.59

Number of poles	Rated operat. current [A] DC 21B 2x660 V / 2x1000 V	Type	Order number	Weight/unit [kg]
Up to 2x660 VDC or 2x1000 VDC				
Includes selector type red-yellow handle (I-O and ON-OFF indication)				
4	16 / 10	OTDCP16SA22M	1SCA125094R1001	0.63
4	25 / 16	OTDCP25SA22M	1SCA125091R1001	0.63
4	32 / 20	OTDCP32SA22M	1SCA125090R1001	0.63
Includes selector type black handle (I-O and ON-OFF indication)				
4	16 / 10	OTDCP16S22M	1SCA125095R1001	0.63
4	25 / 16	OTDCP25S22M	1SCA125092R1001	0.63
4	32 / 20	OTDCP32S22M	1SCA125093R1001	0.63