





η_{ef} (lm/W)
104-117



SPMN 190



SPMN KN



SPMN KO

Vestavné kruhové svítidlo

Těleso:

Bíle lakovaný (RAL 9003) ocelový plech

Optický systém:

Světlovodivá akrylátová deska + mikroprizmatický kryt

Aplikace:

- vestavná montáž do SDK nebo minerálního podhledu

SPMN MULTI	W	lm		Ø	C		kg
		KO	KN				
SPMN2000 E190 MULTI	12 • 15 • 17 • 19	1 250 • 1 450 • 1 650 • 1 850	1 350 • 1 550 • 1 750 • 1 950	210	46	190	0,9
SPMN3000 E370 MULTI	14 • 19 • 23 • 28	1 400 • 1 900 • 2 400 • 2 900	1 500 • 2 000 • 2 500 • 3 000	390			2,0
SPMN4000 E370 MULTI	27 • 31 • 34 • 40	2 900 • 3 600 • 3 700 • 4 050	3 000 • 3 400 • 3 800 • 4 400			370	

SPMN	W	lm		Ø	C		kg
		KO	KN				
SPMN1000 E190	9	970	1 050	210	46	190	0,9
SPMN1500 E190	13	1 350	1 450				
SPMN2000 E190	19	1 800	1 950				
SPMN3000 E370	26	2 800	3 000	390		370	2
SPMN4000 E370	34	3 550	3 800				

lm - světelný výkon svítidla

2200	2700	3000	4000	5700	6500	MIX	RGB	
×	○	○	●	○	×	×	×	×
ON OFF	1-10V	DALI	Bluetooth	Bluetooth		INT	EXT	
●	×	○	×	×	×	×	○	×

● standard

○ volitelné

×

ÚCHYT DO PODHLEDU

PROFIL SVÍTLIDLA

DETAIL KRYTU

