

*ETITEC V T2 255/20 3+1



Specifikace

Kód ETI	002442957
Popis	*ETITEC V T2 255/20 3+1
Typ	T2
AC max continuous operating voltage Uc	255V
Impulzní proud Iimp(10/350ms) (kA)	0kA
In (8/20)	20kA
Max. výbojový proud Imax(8/20ms) (kA)	40kA
Up - Úroveň ochrany napětí (kV)	1.5kV
Svodový proud	Ne
Aplikovaná technologie	MOV,GDT
Dálková signalizace	Ne
Typ sítě	TT/TN-S
Počet modulů	4
Vestavná hloubka (mm)	68mm
Funkce	SPD
Skupina katalogu	ETITEC V
Max. back-up fuse for short circuit protection	A

Online stránka produktu 

Další dokumentace



Katalog technických údajů

3D model

2D File

Návod

Prohlášení CE

Eplan file

Mezinárodní klasifikace ETIM

Klasifikace	EC000941
Název třídy	Surge protection device for power supply systems
System configuration DC	Ne
System configuration IT	Ne
System configuration TN-C	Ne
System configuration TN-S	Ano
System configuration TT	Ano
System configuration other	Ne
Nominal discharge surge current (8/20)	20kA
Nominal voltage AC	230V
Short-circuit breaking capacity (Iscbr)	25kA
Max. continuous voltage AC	255V
Max. discharge surge current (8/20)	40kA
Mounting method	DIN rail (top hat rail) 35 mm
Max. conductor cross section solid (solid, stranded)	35mm ²
Max. conductor cross section flexible (fine-strand)	25mm ²
With remote signalling contact	Ne
Integrated backup fuse	Ne
Signalling at the device	Optical
Category type 2	Ano
Degree of protection (IP)	IP20

Rozměrový výkres

