


Sylvania Granit 0-10V
Granit IP65 0-10V 32000lm 840 MB
0039739

Image not found.

Product features

- Integrated LED highbay; Black aluminium housing; 32000Lm; 200 W; 160 Lm/W; 4000K; Drive current: 780mA; CRI 80; 55° beam angle; 0-10V dimmable; IP65; IK08; Lifespan L80:B20 92,000 hrs; (D x H) 370 x 163 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.



PRODUCT OVERVIEW

Product name	Granit IP65 0-10V 32000lm 840 MB
Technology	LED
Cap/Base	N/A
General application	Logistics & Industry
ETIM Class	EC001716
Warranty	5 years
Fixture luminous flux (lm)	32000
Luminaire efficacy (lm/W)	160
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	55
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	200
Electrical protection	Class I
Dimmable	Yes
Dimming method	0-10V
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Product EAN number	5410288397399

DATA TABLE

General data	
Product name	Granit IP65 0-10V 32000lm 840 MB
Technology	LED
Cap/Base	N/A
General application	Logistics & Industry

Sylvania Granit 0-10V

Granit IP65 0-10V 32000lm 840 MB

0039739

Operating temperature range (°C)	-30°C...+50°C
ETIM Class	EC001716
Warranty	5 years

Optical data

Fixture luminous flux (lm)	32000
Luminaire efficacy (lm/W)	160
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	55
Distribution type	Symmetric
Glare control	< 22
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	200
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	10
Electrical protection	Class I
No. Of switching cycles before premature failures	>100000
Dimmable	Yes
Dimming method	0-10V
Drive current (mA)	780
Inrush Current (A)	100
Inrush Duration (µs)	300
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	4
Max. products per 13A C Breaker	5
Max. products per 16A C Breaker	7
Max. products per 20A C Breaker	9
Max. products per 10A B Breaker	2
Max. products per 13A B Breaker	6
Max. products per 16A B Breaker	4
Max. products per 20A B Breaker	5
Mains surge immunity (differential mode - > L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

Sylvania Granit 0-10V
Granit IP65 0-10V 32000lm 840 MB
0039739

Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B20	92000
Lifespan L90 B50	51000

Physical data

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Nominal Product Height (mm)	163
Nominal Product Diameter (mm)	370
Weight (kg)	2.865


Packaging

Product EAN number	5410288397399
Packaging single length / height (cm)	40.0
Packaging single width (cm)	40.0
Packaging single depth (cm)	14.5
DUN14 (inner)	05410288397399
Units per outer package	1
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	40.0
Packaging outer depth (cm)	14.5

Safety data

Optimal operating condition (°C)	-30-50
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS

Sylvania Granit 0-10V

Granit IP65 0-10V 32000lm 840 MB

0039739

