

Specifikace



Eaton EP-502131

Eaton CR Installation contactor, 20A, 230V AC, 1NO

Obecné specifikace

PRODUCT NAME	Eaton CR contactor
CATALOG NUMBER	EP-502131
EAN	9010653072034
PRODUCT LENGTH/DEPTH	65 mm
PRODUCT HEIGHT	85 mm
PRODUCT WIDTH	17.5 mm
PRODUCT WEIGHT	0.13 kg
CERTIFICATIONS	CE
MODEL CODE	CR2010230A

Technické údaje produktu

AMPERAGE RATING	20 A
FEATURES	Additional equipment possible
DEGREE OF PROTECTION	IP20
INCANDESCENT LAMP LOAD - MAX	1950 W
LOAD FLUORESCENT LAMP - MAX	910 VA
LOAD FLUORESCENT LAMP (DUO CIRCUIT) - MAX	1160 VA
LOAD FLUORESCENT LAMP (PARALLEL COMPENSATED) - MAX	232 VA
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
NUMBER OF MODULAR SPACINGS	1
RATED OPERATING VOLTAGE (UE) - MAX	230 V
RATED OPERATING VOLTAGE (UE) - MIN	230 V
VOLTAGE RATING (EXCITATION) - MAX	230 V
VOLTAGE RATING (EXCITATION) - MIN	230 V
BUILT-IN DEPTH	60 mm
VOLTAGE TYPE	AC AC/DC
UTILIZATION CATEGORY (ACCORDING TO EN IEC 60947-4-1)	AC-1

Zdroje

DECLARATIONS OF
CONFORMITY

[eaton-contactor-
declaration-of-conformity-
eu250193en.pdf](#)

NÁZEV PROJEKTU:

ČÍSLO PROJEKTU:

PŘIPRAVIL:

DATUM:



Eaton Corporation Plc. Eaton House
30 Pembroke Road
Dublin 4, Irsko
Eaton.com

© 2026 Eaton. Všechna práva vyhrazena.

Sledujte nás na sociálních sítích,
abyste získali nejnovější informace o
produktech a podpoře.

