

ETITEC ML T123 300/12,5 3+0 RC



Specifikace

Kód ETI	002440666
Popis	ETITEC ML T123 300/12,5 3+0 RC
Funkce	SPD
Typ	T1, T2, T3
Impulzní proud Iimp(10/350ms) (kA)	12,5
Max. výbojový proud Imax(8/20ms) (kA)	40
Dálková signalizace	TRUE
Typ sítě	TN-C
Skupina katalogu	ETITEC ML
In (8/20)	20
Počet modulů	3
Up - Úroveň ochrany napětí (kV)	1,5
Svodový proud	Ano
Aplikovaná technologie	MOV
Vestavná hloubka (mm)	70
AC max continous operating voltage Uc	300

[Online stránka produktu](#)

Další dokumentace

[Katalog technických údajů](#)[3D model](#)[Návod](#)[Prohlášení CE](#)[Eplan file](#)

Mezinárodní klasifikace ETIM

Klasifikace	EC001457
Název třídy	Combined arrester for power supply systems
System configuration DC	
System configuration IT	
System configuration TN-C	1
System configuration TN-S	
System configuration TT	
System configuration other	
Number of poles	3
Lightning impulse current (10/350 μ s)	12,5
Max. continuous voltage AC	300
Nominal voltage AC	230
Voltage protection level	1,5
Specific energy (W/R)	39
Max. conductor cross section solid (solid, stranded)	35
Max. conductor cross section flexible (fine-strand)	25
Mounting method	DIN rail (top hat rail) 35 mm
Construction size	3 modular spacing
Remote signalling	1
Signalling at the device	Optical
Test class	Type 1 + 2
Exhausting	
Integrated backup fuse	
Degree of protection (IP)	IP20