

Technical Data Sheet

Date: 03/11/2022

4x32A CEE Norm Plug

Ref. No: 3026-301-1601



Pack Unit

10



Weight

212 gr.




Technical Informations

Quick Connection

Ampere	32A
Voltage	380 - 415 V. AC
Hertz	50 - 60 Hz
Protection Class	IP 44
Clock Position	6h
Number Of Poles	4 (3P + E)
Contact Material	Brass (CuZn)
Housing Material	PA6
Connection Type	Quick
Operation Temp. (-25 / + 40 IEC 60309)	-25 / +80 (1 hour -100° C)

Dimensions

a	149
b	100
c	63
Ød	11-20,5
Cable Diameter (Min.)	2,5 mm²
Cable Diameter (Max.)	6 mm²



Different Earth Contact Positions (Clock Positions)

>50V 300-500 Hz 2h	380V-50 Hz 440V-60Hz 3h	100-130V 50-60 Hz 4h	600-690V 50-60 Hz 5h	380-415V 50-60 Hz 6h	480-500V 50-60 Hz 7h	200-250V 50-60 Hz 9h	>50V 100-300 Hz 10h	440-460V 60 Hz 11h
3026-301-1100-2h	3026-301-1600-3h	3026-301-0700-4h	3026-301-0300-5h	3026-301-1600	3026-301-0300-7h	3026-301-0900-9h	3026-301-1100-10h	3026-301-1600-11h



Tel: +90 232 880 90 01
Fax: +90 232 880 90 02



info@tpelectric.com.tr



Kemalpaşa O.S.B. 600 Sk. No:364
35730 Kemalpaşa - İZMİR / TÜRKİYE