

Cable reel, 4x 2P+E sockets, PVC, H05VV-F 3x1.5mm² - 50m, fixed sockets, anti-twist system, overload protection



Marka: Orno | Symbol: OR-AE-13292/50M | Ean: 5908254804465



PRODUCT DESCRIPTION

The cable reel enables to safely and reliably connect more devices to a single extension cord. It is equipped with 4 French-type sockets (2P+E) with safety shutters, which ensure convenience and compatibility with various electrical appliances.

Thanks to its durable construction made from high-quality plastic and a single thermal switch serving as overload protection, it ensures peace of mind and safety when connecting more appliances to one extension socket. The PVC insulation guarantees durability and reliability of use.

The PVC cable 50m long with H05VV-F 3x1,5mm² specification provides flexibility and freedom of use, without worrying about being too far from an outlet. The cable reel has current protection which guarantees smooth operation even while intensive use. The maximum load is 1100W/4,8A when the cable is coiled, and 3200W/13,9A when the cable is uncoiled.

The anti-twist system (fixed sockets) is an innovative feature designed to eliminate cable twisting during use, especially when four devices are connected at the same time.

A convenient handle for carrying as well as crank handle for winding the cable provide ergonomics and comfort during transport.

The dimensions measure 247x341mm Black and dark blue colour.

TECHNICAL DATA

General information:

Housing material:	Tworzywo sztuczne
Cable assembly:	H05VV-F
Core cross section [mm]:	1.5
Number of cores:	3
Number of socket outlets with protective contact (french):	4
Cable length [m]:	50
With mounting frame:	Tak
With thermal overload protection:	Tak
Fixed sockets:	Tak
Protection:	Wyłącznik nadprądowy
Degree of protection (IP):	IP20
Colour:	czarno-granatowy
Supply voltage [V]:	230

Frequency [Hz]:	50
Current [A]:	16
Socket type:	2P+Z
Socket standard:	french (type E)
Shutters for current paths:	Tak
Max. Load/current c cable rolled up:	1100W/4,8A
Max. Load/current cable unrolled:	3200W / 13,9A
Insulation type:	PVC



