

# PRODUCT DATASHEET

## URB LTRN V 29W SYM PS 830-840 IP66 GY

URBAN LANTERN SYMMETRIC | Fitting area lighting applications



VALUE  
CLASS

### Areas of application

- Replacement for luminaires with mercury vapor or metal halide lamps
- Streets
- Residential installations
- Pedestrian zones
- Parks
- Public areas

### Product benefits

- Highly versatile due to selectable CCT and power steps (Power Select - PS)
- Low flicker light thanks to special electronic control gear
- Energy savings thanks to system efficacy of up to 139 lm/W
- Bright, robust and durable

### Product features

- Protection class: II
- Lifetime (L80/B10): up to 100,000 h (at 25 °C)
- Type of protection: IP66
- Impact resistance: IK10
- Symmetric light distribution

## TECHNICAL DATA

### Electrical data


|                                                             |                                           |
|-------------------------------------------------------------|-------------------------------------------|
| Nominal wattage                                             | 29 W / 25 W / 20.0 W / 15 W <sup>1)</sup> |
| Nominal voltage                                             | 220...250 V                               |
| Mains frequency                                             | 50...60 Hz                                |
| Nominal current                                             | 70-90-110-130 mA                          |
| Inrush current                                              | 25.8 A                                    |
| Inrush current time T <sub>h50</sub>                        | 330 µs                                    |
| Max. number of luminaires per miniature circuit breaker B16 | 8                                         |
| Max. number of luminaires per miniature circuit breaker C10 | 8                                         |
| Max. number of luminaires per miniature circuit breaker C16 | 13                                        |
| Power factor $\lambda$                                      | > 0.90                                    |
| Total harmonic distortion                                   | < 20 %                                    |
| Protection class                                            | II                                        |
| Surge capability (L-N)                                      | 6 kV                                      |
| Operating mode                                              | Integrated LED driver                     |

<sup>1)</sup> For possible options refer to lumen/power table image

### Photometrical data

|                                              |                                                     |
|----------------------------------------------|-----------------------------------------------------|
| Luminous flux                                | 3945 lm / 3400 lm / 2720 lm / 2040 lm <sup>1)</sup> |
| Luminous efficacy                            | 136 lm/W <sup>1)</sup>                              |
| Color temperature                            | 3000 K / 4000 K                                     |
| Light color (designation)                    | Warm White / Cool White                             |
| Color rendering index Ra                     | 80                                                  |
| Standard deviation of color matching         | 5 sdcm                                              |
| Low flicker                                  | Yes                                                 |
| Flickering metric (Pst LM)                   | <1                                                  |
| Stroboscope effect metric (SVM)              | <0.4                                                |
| Photobiological safety group acc. to EN62778 | RG1                                                 |
| Beam angle                                   | 145 °                                               |


<sup>1)</sup> For possible options refer to lumen/power table image



URB LTRN V 29/59W SYMPS

Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 395.00 mm |
| Height         | 417.00 mm |
| Product weight | 4155.00 g |
| Cable length   | 250 mm    |



URBAN LANTERN

Materials & Colors

|                                            |                    |
|--------------------------------------------|--------------------|
| Product color                              | Gray               |
| Housing color                              | Gray               |
| Body material                              | Aluminum           |
| Cover material                             | Polycarbonate (PC) |
| Light emitting surface material            | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 750 °C             |
| Mercury content                            | 0.0 mg             |

Application & Mounting

|                              |              |
|------------------------------|--------------|
| Ambient temperature range    | -30...+50 °C |
| Temperature range at storage | -35...+80 °C |

|                                        |               |
|----------------------------------------|---------------|
| Type of connection                     | Cable, 3-pole |
| Type of protection                     | IP66          |
| Protection class IK (shock resistance) | IK10          |
| Dimmable                               | No            |
| Mounting type                          | Post top      |
| Mounting location                      | Pole          |
| Application environment                | Outdoor       |
| Adjustable                             | No            |
| With light source                      | Yes           |

### Lifespan

|                            |                        |
|----------------------------|------------------------|
| Lifespan L70/B50 at 25 °C  | 100000 h <sup>1)</sup> |
| Lifespan L80/B10 at 25 °C  | 100000 h <sup>1)</sup> |
| Lifespan L80/B50 at 25 °C  | 100000 h               |
| Lifespan L90/B10 at 25 °C  | 68000 h                |
| Number of switching cycles | 100000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Control gear

|                             |                          |
|-----------------------------|--------------------------|
| Output current              | 765...650...520...390 mA |
| ECG - Output ripple current | < 20 %                   |

### Certificates & Standards

|                                                      |                        |
|------------------------------------------------------|------------------------|
| Standards                                            | CE / UKCA / EAC / ENEC |
| Luminaire with limited surface temperature, "D sign" | No                     |
| Ball shot safe                                       | No                     |
| Replaceable light source (EPREL)                     | Not replaceable        |

### Additional product data

|                |              |
|----------------|--------------|
| Added function | MULTI SELECT |
| BEG subsidy    | No           |

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name              |
|------------------------------------------------------------------------------------|----------------------------------------|----------------------------|
|  | User instruction / safety instructions | URBAN LANTERN              |
|  | Legal information                      | Legal Insert URBAN LANTERN |

| Documents and certificates                                                         |                                     | Document name                                         |
|------------------------------------------------------------------------------------|-------------------------------------|-------------------------------------------------------|
|    | Legal information                   | URBAN LANTERN                                         |
|    | Legal information                   | Informationstext 18 Abs 4 ElektroG                    |
|    | Declarations of conformity          | CE Declaration URBAN LANTERN                          |
|    | Declarations of conformity UKCA     | UKCA Declaration URBAN LANTERN                        |
| Photometric and lighting design files                                              |                                     | Document name                                         |
|    | IES file (IES)                      | URBAN LANTERN V 29W SYM PS 830 IP66 GY                |
|    | IES file (IES)                      | URBAN LANTERN V 29W SYM PS 840 IP66 GY                |
|    | LDT file (Eulumdat)                 | URBAN LANTERN V 29W SYM PS 830 IP66 GY                |
|   | LDT file (Eulumdat)                 | URBAN LANTERN V 29W SYM PS 840 IP66 GY                |
|  | ULD file (DIALux)                   | URB LTRN V 29W SYMPS830-840 IP66 GY                   |
|  | Light distribution curve type polar | URB LTRN V 29/59W SYMPS                               |
| CAD/BIM files                                                                      |                                     | Document name                                         |
|  | BIM Revit 3D                        | Urban Lantern                                         |
|  | CAD STEP 3D                         | SL URBAN LANTERN                                      |
|  | CAD STEP 3D                         | URB LTRN                                              |
| Tender texts                                                                       |                                     | Document name                                         |
|  | Tender documents                    | URBAN LANTERN SYMMETRIC 29W SYM PS 830 840 IP66 GY-EN |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854246838 | Shipping box<br>1            | 435 mm x 435 mm x 220 mm             | 4520.00 g    | 41.63 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

| Ref.    | 15   | 20   | 25   | 30   | 35   | 40   | 45   | 50   | 55   | 60   | 65   | 70   | 75   | 80   | 85   | 90   | 95   | 100  |
|---------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Typical | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 |
| min     | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  | 150  |
| W       | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 | 8000 |

References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.