


QUADRO UGR16 600x600 MULTIPOWER 2250-4650LM 840

Item No: 0047250

SYLVANIA

PROTM



Unique stylish recessed modular Led luminaire, ideal for general indoor lighting applications such as breakout areas, offices and meeting rooms. Steel frame with integrated reflector, passive cooling. Low glaring UGR<16. RG1, 75 degree beam angle , optical system: white painted reflector with total internal reflection lenses. Light color temperature: 4000K Neutral White, total system power: 34W , total fixture output: 4650lm, efficacy: 150 lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), lifespan: 77,000 hours at 80% of the original output (L80B20), IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, low flicker, non-dimmable 8-step Multipower driver (15W 2250lm, 18W 2650lm, 21W 3150lm, 24W 3500lm, 27W 3950lm, 30W 4250lm, 32W 4500lm, 34W 4650lm), electrical protection: Class II. Degree of Protection: IP40/IP20, suitable for indoor environment only. Nominal size: 595x595mm, Loop in / loop out wiring, safety cables included, 18mm nominal height, RAL 9003 - Signal white color frame, weight: 3,2Kg.


QUADRO UGR16 600x600 MULTIPOWER 2250-4650LM 840

Item No: 0047250

SYLVANIA

Technical Assets


Dimensions (mm)



Photometrics

| Distance [m] | Cone diameter [m] | E10' | E15' | E30' | E60' |
|--------------|-------------------|------|------|------|------|
| 0.5 | 0.75 0.75 | 8419 | 1959 | 367" | 1891 |
| 1.0 | 1.49 1.50 | 1904 | 478 | 367" | 473 |
| 1.5 | 2.24 2.25 | 713 | 154 | 367" | 153 |
| 2.0 | 2.98 3.00 | 401 | 104 | 367" | 103 |
| 2.5 | 3.73 3.75 | 267 | 88 | 367" | 88 |
| 3.0 | 4.47 4.50 | 173 | 68 | 367" | 68 |

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 73.8°)
 — C90 - C270 (Half beam angle: 73.4°)



General data

| | |
|---|---|
| Product name | QUADRO UGR16 600x600 MULTIPOWER 2250-4650LM 840 |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Steel |
| Mount | Ceiling recessed mounting, Suspended |
| General application | Education, Office |
| Operating temperature range (°C) | -10°C...+50°C |
| Performance ambient temperature Tq (°C) | 25 |
| ETIM Class | EC002892 |
| E-number FI | 4278095 |
| Warranty | 5 years |

Optical data

| | |
|--|---------------|
| Fixture luminous flux (lm) | 4650 |
| Luminaire efficacy (lm/W) | 137 |
| LOR (%) | 100 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Neutral White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 75 |
| Distribution type | Symmetric |
| Glare control | < 16 |
| Photobiological Risk Group | RG1 |
| Lumen maintenance at end of nominal life (%) | 70 |

QUADRO UGR16 600x600 MULTIPOWER 2250-4650LM 840

Item No: 0047250

SYLVANIA

Electrical data

| | |
|--|------------------------------|
| Total power consumption (W) | 34 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Lamp power factor | 0.95 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 25.0 |
| Electrical protection | Class II |
| Control gear required | No |
| Control gear type | Electronic ballast multiwatt |
| No. Of switching cycles before premature failures | >100000 |
| Dimmable | No |
| Dimming method | N/A |
| Drive current (mA) | 155 |
| Inrush Current (A) | 40 |
| Inrush Duration (µs) | 150 |
| Energy Efficiency Class (A->G) of contained light source | E |
| Nominal Frequency (Hz) | 50/60Hz |
| LED Flickering Rate | Ultra low (5% or less) |
| Max. products per 10A C Breaker | 38 |
| Max. products per 13A C Breaker | 48 |
| Max. products per 16A C Breaker | 60 |
| Max. products per 20A C Breaker | 75 |
| Max. products per 10A B Breaker | 32 |
| Max. products per 13A B Breaker | 41 |
| Max. products per 16A B Breaker | 52 |
| Max. products per 20A B Breaker | 64 |

Lifetime data

| | |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B20 | 77000 |

Physical data

| | |
|-----------------------------|-------------------------|
| Housing colour | RAL 9003 - Signal white |
| IP rating | IP40/20 |
| IK rating | IK08 |
| Diffuser material | None |
| Nominal Product Length (mm) | 595 |
| Nominal Product Width (mm) | 595 |
| Nominal Product Height (mm) | 18.8 |
| Weight (kg) | 2.826 |
| Recessed Depth (mm) | 60 |

Packaging

| | |
|---------------------------------------|----------------|
| Product EAN number | 5410288472508 |
| Packaging single length / height (cm) | 60.5 |
| Packaging single width (cm) | 2.8 |
| Packaging single depth (cm) | 66.7 |
| DUN14 (inner) | 15410288472505 |
| Units per outer package | 1 |
| Packaging outer length / height (cm) | 60.5 |
| Packaging outer width (cm) | 2.8 |
| Packaging outer depth (cm) | 66.7 |

Safety data

| | |
|----------------------------------|--------|
| Glow Wire Test (°C) | 650 |
| Optimal operating condition (°C) | -10-50 |