

Specifikace



Foto je ilustrační



Eaton 189984

Eaton Moeller® series DILEM Contactor, 24 V DC, 3 pole, 380 V 400 V, 4 kW, Contacts N/O = Normally open= 1 N/O, Screw terminals, DC operation DILEM-10-G-EA(24VDC)

General specifications

PRODUCT NAME	Eaton Moeller® series DILEM Mini contactor
CATALOG NUMBER	189984
EAN	4015081879809
PRODUCT LENGTH/DEPTH	54 mm
PRODUCT HEIGHT	58 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.206 kg
COMPLIANCES	CE CE Marked RoHS conform
MODEL CODE	DILEM-10-G-EA(24VDC)



Powering Business Worldwide

Features & Functions

NUMBER OF POLES	Three-pole
-----------------	------------

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
--	--------

AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
-----------------------------------	--------

Magnet system

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	24 V
---	------

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	24 V
---	------

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0.9 W
--	-------

HEAT DISSIPATION CAPACITY PDISS	0 W
---------------------------------	-----

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.3 W
---	-------

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	2.3 W
--	-------

General

VOLTAGE TYPE	DC
--------------	----

Electrical rating

RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	4 kW
---	------

RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V	22 A
---	------

RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V	9 A
---	-----

Contacts

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
---	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	1
---	---

Zdroje

DECLARATIONS OF CONFORMITY	eaton-mini-contactor-declaration-of-conformity-uk251244en.pdf
----------------------------	---

	eaton-mini-contactor-declaration-of-conformity-eu250761en.pdf
--	---

ECAD MODEL	ETN.189984.edz
------------	--------------------------------

CHARACTERISTIC CURVE	eaton-contactors-switch-dilm-characteristic-curve.eps
----------------------	---

	eaton-contactors-switch-dilm-characteristic-curve-002.eps
--	---

INSTALAČNÍ NÁVODY	IL034040ZU
-------------------	----------------------------

MCAD MODEL	DA-CS-dil_em
------------	------------------------------

	DA-CD-dil_em
--	------------------------------

PEP ECO-PASSPORT	eaton-iec-contactors-pep-eato-00136-v0101-en.pdf
------------------	--

SCHÉMATA ZAPOJENÍ	eaton-contactors-contact-dilm-wiring-diagram.eps
-------------------	--

NÁZEV PROJEKTU:

ČÍSLO PROJEKTU:

PŘIPRAVIL:

DATUM:



Eaton Corporation Plc. Eaton House
30 Pembroke Road
Dublin 4, Irsko
Eaton.com

© 2025 Eaton. Všechna práva vyhrazena.

Sledujte nás na sociálních sítích,
abyste získali nejnovější informace o
produktech a podpoře.

