







Front Mounting Switches

sälzer



Product lines
B200-A/ -D

Front mounting switch

Four hole mounting
36 x 36 mm

033N1 (IP66)
033N4 (IP66)

Complete switch	Poles	Product lines	Rated data (IEC 60947)			Order code number
			Operational current I _e	Operational power at 380–440 V		
			AC-21A A	AC-23A kW	AC-3 kW	
Main Switches	3 ... 8	B200-A/ -D	50	18,5	15	B250 - 41 ... - 033N1
OFF position padlockable 09h			63	22	18,5	B263 - 41 ... - 033N1
Main/Emergency-OFF Switches	3 ... 8	B200-A/ -D	50	18,5	15	B250 - 41 ... - 033N4
OFF position padlockable 09h			63	22	18,5	B263 - 41 ... - 033N4

SMD modules for basic switch A01

Mounting form module for 033N.

B200-A/ -D

BFB2 - 033

N-padlock device 67 x 67 mm, mounting form 033N1
Escutcheon black, padlockable handle black

2CN1

N-padlock device 67 x 67 mm, mounting form 033N4
Escutcheon yellow, padlockable handle red

2CN4

Dimensions (mm)

Product lines	A	B	B1	B2	C	C1	D1	D2	E	H
B200-A	67	50	69	88	58	33	15	4,5	36	72
B200-D	67	100	119	138	70	33	15	4,5	36	72