OMRON Průmyslová automatizace

E3FA-DP12 5M

Photoelectric sensor, M18 threaded barrel, plastic, red LED, diffuse, 300 mm, PNP, Light-ON/Dark-ON, 5 m cable

Technické údaje

Shape	Cylindrical axial
Sensing method	Diffuse reflective
Sensing distance	300 mm
Setting method	Manual adjustment
Connection method	Cable
Cable length	5 m
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	0.5 ms
Material housing	ABS
Thread size	M18
Product Length (unpacked)	41 mm
Type of light	Polarity free red light
Power supply voltage	10-30 V
Degree of protection (IP)	IP67/IP69K

Příslušenství

	E39-L182	E3FA/R flush mounting bracket
	E39-L183	M18 L-type mounting bracket, stainless steel (SUS304)

Stahování dokumentace

CAD knihovny

E3FA Cylindrical Photoelectric Sensors

Brožura

EN PDF 9,1 MB

E3FA-____

Instrukční manuál

EN PDF 371,7 KB

E3FA/E3RA/E3FB/E3RB Photoelectric Sensors

Katalogový list

EN PDF 6,4 MB

EAC Mark removal

Upozornění na ukončení výroby

EN PDF 220,8 KB

PODMÍNKY POUŽÍVÁNÍ WEBOVÝCH STRÁNEK

Tento dokument ve formátu PDF byl 15 January, 2026 vytvořen z webových stránek společnosti OMRON určených pro evropský trh a věnujících se průmyslové automatizaci. Kliknutím sem zobrazíte právní podmínky.