

MAJ1096E10



Připojovací svorka OL 95T Al/Cu 1x25-95mm²

-

Připojovací svorka OL 95T Al/Cu  
1x25-95mm²

|                  |                          |
|------------------|--------------------------|
| Kód produktu     | MAJ1096E10               |
| EAN              | 4744397014757            |
| Třída ETIM       | EC000897                 |
| Produktová řada  | Heavy duty connectors OL |
| Celní kód CN8    | 85369010                 |
| Jednotka         | ks                       |
| Velikost balení: | 15                       |
| Hmotnost         | 0,069 kg                 |
| Délka            | 0,05 m                   |
| Šířka            | 0,018 m                  |
| Výška            | 0,033 m                  |

|                                                                          |                         |
|--------------------------------------------------------------------------|-------------------------|
| Connectable conductor cross section fine-strand without cable end sleeve | 25 - 95 mm²             |
| Connectable conductor cross section fine-strand with cable end sleeve    | 25 - 95 mm²             |
| Connectable conductor cross section solid-core                           | Nelze použít            |
| Connectable conductor cross section multi-wired                          | 25 - 95 mm²             |
| Rated current In                                                         | 320 A                   |
| Rated voltage                                                            | 690 V                   |
| Type of electrical connection 1                                          | Screw connection        |
| Type of electrical connection 2                                          | Flat plug-in connection |
| Number of levels                                                         | 1                       |
| Number of clamp positions per level                                      | 1                       |
| Mounting method                                                          | Other                   |
| Material insulation body                                                 | None                    |
| Operating temperature                                                    | -- 80 °C                |
| Inflammability class of insulation material according to UL94            | -                       |
| Width                                                                    | 18 mm                   |
| Height                                                                   | 33 mm                   |
| Depth                                                                    | 50 mm                   |
| Explosion-tested version 'Ex e'                                          | Ne                      |
| Closing plate required                                                   | Ne                      |
| Colour                                                                   | Other                   |
| Internally connected stages                                              | Ano                     |

