

Communicative damper actuator for adjusting dampers in technical building installations

- Air damper size up to approx. 2 m²
- Torque motor 10 Nm
- Nominal voltage AC/DC 24 V
- Control modulating, communicative
- Running time motor 35 s
- Communication via Belimo MP-Bus
- Conversion of sensor signals



Picture may differ from product

Technical data

Electrical data	
	Nominal voltage
	AC/DC 24 V
	Nominal voltage frequency
	50/60 Hz
	Nominal voltage range
	AC 19.2...28.8 V / DC 21.6...28.8 V
	Power consumption in operation
	4 W
	Power consumption in rest position
	1.5 W
	Power consumption for wire sizing
	7 VA
	Connection supply / control
	Cable 1 m, 4x 0.75 mm ²
	Parallel operation
	Yes (note the performance data)
Data bus communication	
	Communicative control
	MP-Bus
	Number of nodes
	MP-Bus max. 8
Functional data	
	Torque motor
	10 Nm
	Torque variable
	25%, 50%, 75% reduced
	Operating range Y
	2...10 V
	Input impedance
	100 kΩ
	Operating range Y variable
	Start point 0.5...30 V
	End point 2.5...32 V
	Operating modes optional
	Open/close
	3-point (AC only)
	Modulating (DC 0...32 V)
	Position feedback U
	2...10 V
	Position feedback U note
	Max. 0.5 mA
	Position feedback U variable
	Start point 0.5...8 V
	End point 2.5...10 V
	Position accuracy
	±5%
	Direction of motion motor
	selectable with switch 0/1
	Direction of motion variable
	electronically reversible
	Direction of motion note
	Y = 0 V: At switch position 0 (ccw rotation) / 1 (cw rotation)
	Manual override
	with push-button, can be locked
	Angle of rotation
	Max. 95°
	Angle of rotation note
	can be limited on both sides with adjustable mechanical end stops
	Running time motor
	35 s / 90°
	Running time motor variable
	20...75 s
	Sound power level, motor
	45 dB(A)

Functional data	Adaptation setting range	manual
	Adaptation setting range variable	No action Adaptation when switched on Adaptation after pushing the manual override button
	Override control	MAX (maximum position) = 100% MIN (minimum position) = 0% ZS (intermediate position, AC only) = 50%
	Override control variable	MAX = (MIN + 32%)...100% MIN = 0%...(MAX - 32%) ZS = MIN...MAX
	Mechanical interface	Universal shaft clamp 8...26.7 mm
	Position indication	Mechanical, pluggable
	Protection class IEC/EN	III, Safety Extra-Low Voltage (SELV)
	Power source UL	Class 2 Supply
	Degree of protection IEC/EN	IP54
	Degree of protection NEMA/UL	NEMA 2
Safety data	Housing	UL Enclosure Type 2
	EMC	CE according to 2014/30/EU
	Certification IEC/EN	IEC/EN 60730-1 and IEC/EN 60730-2-14
	UL Approval	cULus according to UL60730-1A, UL60730-2-14 and CAN/CSA E60730-1 The UL marking on the actuator depends on the production site, the device is UL-compliant in any case
	Hygiene test	According to VDI 6022 Part 1 / SWKI VA 104-01, cleanable and disinfectable, low emission
	Type of action	Type 1
	Rated impulse voltage supply / control	0.8 kV
	Pollution degree	3
	Ambient humidity	Max. 95% RH, non-condensing
	Ambient temperature	-30...50°C [-22...122°F]
Weight	Storage temperature	-40...80°C [-40...176°F]
	Servicing	maintenance-free
Weight		0.79 kg

Safety notes



- This device has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- Outdoor application: only possible in case that no (sea) water, snow, ice, insolation or aggressive gases interfere directly with the device and that it is ensured that the ambient conditions remain within the thresholds according to the data sheet at any time.
- Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied with during installation.
- The device may only be opened at the manufacturer's site. It does not contain any parts that can be replaced or repaired by the user.
- Cables must not be removed from the device.
- To calculate the torque required, the specifications supplied by the damper manufacturers concerning the cross-section and the design, as well as the installation situation and the ventilation conditions must be observed.
- The device contains electrical and electronic components and must not be disposed of as household refuse. All locally valid regulations and requirements must be observed.

Product features

Operating mode

Conventional operation:

The actuator is connected with an analogue control signal Y (note the operating range) and drives to the position defined. The measuring voltage U serves for the electrical display of the actuator position 0...100% and as control signal for other actuators.

Operation on Bus:

The actuator receives its digital control signal from the higher level controller via the MP-Bus and drives to the position defined. Connection U serves as communication interface and does not supply an analogue measuring voltage.

Converter for sensors

Connection option for a sensor (passive or active sensor or switching contact). The MP actuator serves as an analogue/digital converter for the transmission of the sensor signal via MP-Bus to the higher level system.

Configurable device

The factory settings cover the most common applications. Single parameters can be modified with Belimo Assistant 2 or ZTH EU.

Simple direct mounting

Simple direct mounting on the damper shaft with a universal shaft clamp, supplied with an anti-rotation mechanism to prevent the actuator from rotating.

Manual override

Manual override with push-button possible (the gear train is disengaged for as long as the button is pressed or remains locked).

Adjustable angle of rotation

Adjustable angle of rotation with mechanical end stops.


High functional reliability

The actuator is overload protected, requires no limit switches in intermediate positions and automatically stops when the end stop is reached (at rest).

Home position

The first time the supply voltage is switched on, i.e. at the time of commissioning, the actuator carries out a synchronisation. The synchronisation is in the home position (0%).

The actuator then moves into the position defined by the control signal.



Product features

Adaptation and synchronisation	<p>An adaptation can be triggered manually by pressing the "Adaptation" button or with Belimo Assistant 2. Both mechanical end stops are detected during the adaptation (entire setting range).</p> <p>Automatic synchronisation after pressing the manual override button is configured. The synchronisation is in the home position (0%).</p> <p>The actuator then moves into the position defined by the control signal.</p> <p>A range of settings can be made using Belimo Assistant 2.</p>
---------------------------------------	--

Accessories

Tools	Description	Type
Service tool, with ZIP-USB function, for configurable and communicative Belimo actuators, VAV controller and HVAC performance devices	ZTH EU	
Service tool for wired and wireless setup, on-site operation and troubleshooting.	Belimo Assistant 2	
Adapter for Service-Tool ZTH	MFT-C	
Connecting cable 5 m, A: RJ11 6/4 LINK.10, B: 6-pin for connection to service socket	ZK1-GEN	
Connecting cable 5 m, A: RJ11 6/4 LINK.10, B: free wire end for connection to MP/PP terminal	ZK2-GEN	
Belimo Assistant Link Bluetooth and USB to NFC and MP-Bus converter for configurable and communicative devices	LINK.10	
Electrical accessories	Description	Type
Auxiliary switch 1x SPDT add-on	S1A	
Auxiliary switch 2x SPDT add-on	S2A	
Feedback potentiometer 140 Ω add-on	P140A	
Feedback potentiometer 1 k Ω add-on	P1000A	
Feedback potentiometer 10 k Ω add-on	P10000A	
Signal converter voltage/current 100 k Ω 4...20 mA, Supply AC/DC 24 V	Z-UIC	
Positioner for wall mounting	SGA24	
Positioner for built-in mounting	SGE24	
Positioner for front-panel mounting	SGF24	
Positioner for wall mounting	CRP24-B1	
MP-Bus power supply for MP actuators	ZN230-24MP	
Gateways	Description	Type
Gateway MP to BACnet MS/TP	UK24BAC	
Gateway MP to Modbus RTU	UK24MOD	
Mechanical accessories	Description	Type
Actuator arm for standard shaft clamp (one-sided)	AH-25	
Shaft extension 240 mm \varnothing 20 mm for damper shaft \varnothing 8...22.7 mm	AV8-25	
Ball joint suitable for damper crank arm KH8	KG8	
Ball joint suitable for damper crank arm KH8 / KH10	KG10A	
Damper crank arm Slot width 8.2 mm, clamping range \varnothing 10...18 mm	KH8	
Shaft clamp one-sided, clamping range \varnothing 8...26 mm with insert, Multipack 20 pcs.	K-ENMA	
Shaft clamp one-sided, clamping range \varnothing 8...26 mm, Multipack 20 pcs.	K-ENSA	
Shaft clamp reversible, clamping range \varnothing 8...20 mm	K-NA	
Form fit insert 8x8 mm, Multipack 20 pcs.	ZF8-NMA	
Form fit insert 10x10 mm, Multipack 20 pcs.	ZF10-NSA	
Form fit insert 12x12 mm, Multipack 20 pcs.	ZF12-NSA	
Form fit insert 15x15 mm, Multipack 20 pcs.	ZF15-NSA	
Form fit insert 16x16 mm, Multipack 20 pcs.	ZF16-NSA	
Mounting kit for linkage operation for flat installation	ZG-NMA	
Anti-rotation mechanism 180 mm, Multipack 20 pcs.	Z-ARS180	
Baseplate extension for NM..A to NM..	Z-NMA	
Position indicator, Multipack 20 pcs.	Z-PI	

Electrical installation



Supply from isolating transformer.

Parallel connection of other actuators possible. Observe the performance data.

Wire colours:


1 = black

2 = red


3 = white

5 = orange

MP-Bus



AC/DC 24 V, modulating




1	2	3	0 %	100 %
↙ ↘	↙ ↘	↙ ↘	↙ ↘	↙ ↘
↙ ↘	↙ ↘	↙ ↘	↙ ↘	↙ ↘

Further electrical installations

Functions with basic values (conventional mode)


Override control with AC 24 V with relay contacts

Override control with AC 24 V with rotary switch





1	2	a	b	c	
↙ ↘	↙ ↘	↙ ↘	↙ ↘	↙ ↘	0 %
↙ ↘	↙ ↘	↙ ↘	↙ ↘	↙ ↘	ZS 50 %
↙ ↘	↙ ↘	↙ ↘	↙ ↘	↙ ↘	100 %
↙ ↘	↙ ↘	↙ ↘	↙ ↘	↙ ↘	Y

e.g. 1N 4007




Functions with basic values (conventional mode)


Control remotely 0...100% with positioner SG..



Primary/secondary operation (position-dependent)



Control with 4...20 mA via external resistor




Caution:

The operating range must be set to DC 2...10 V.
The 500 Ohm resistor converts the 4...20 mA current signal to a voltage signal DC 2...10 V.

Functions with basic values (conventional mode)

Functional check




Procedure

1. Connect 24 V to connections 1 and 2
2. Disconnect connection 3:
 - With direction of rotation 0: Actuator rotates to the left
 - With direction of rotation 1: Actuator rotates to the right
3. Short-circuit connections 2 and 3:
 - Actuator runs in opposite direction

MP-Bus


MP-Bus Network topology



There are no restrictions for the network topology (star, ring, tree or mixed forms are permitted). Supply and communication in one and the same 3-wire cable


- no shielding or twisting necessary
- no terminating resistors required

Connection on the MP-Bus




Max. 8 MP-Bus nodes

Connection of active sensors



- Supply AC/DC 24 V
- Output signal 0...10 V (max. 0...32 V)
- Resolution 30 mV

Connection of external switching contact




- Switching current 16 mA @ 24 V
- Start point of the operating range must be configured on the MP actuator as ≥ 0.5 V

Further electrical installations

MP-Bus

Connection of passive sensors



Ni1000	-28...+98°C	850...1600 Ω ²⁾
PT1000	-35...+155°C	850...1600 Ω ²⁾
NTC	-10...+160°C ¹⁾	200 Ω ...60 k Ω ²⁾

1) Depending on the type


2) Resolution 1 Ohm

Compensation of the measured value is recommended


Functions with specific parameters (configuration necessary)

Override control and limiting with AC 24 V with relay contacts

Control open/close




1	2	a	b	c	d	e	
							Close
							MIN
							ZS
							MAX
							Open
							Y




Override control and limiting with AC 24 V with rotary switch

Control 3-point with AC 24 V




Caution:
The "Close" function is only guaranteed if the start point of the operating range is defined as min. 0.5 V.



1	2	3 (a)	3 (b)		
					
					
					
					
				stop	stop
					

Operating controls and indicators

**1 Direction-of-rotation switch**

Switch over: Direction of rotation changes

2 Push-button and LED display green

Off: No power supply or malfunction

On: In operation

Press button: Triggers angle-of-rotation adaptation, followed by standard mode

3 Push-button and LED display yellow

Off: Standard mode

On: Adaptation or synchronisation process active

Flickering: MP-Bus communication active

Flashing: Request for addressing from MP client

Press button: Confirmation of the addressing

4 Manual override button

Press button: Gear train disengages, motor stops, manual override possible

Release button: Gear train engages, synchronisation starts, followed by standard mode

5 Service plug

For connecting configuration and service tools

Check power supply connection

2 Off and **3** On Possible wiring error in power supply


Service

Wired connection

The device can be configured by ZTH EU via the service socket.

For an extended configuration, Belimo Assistant 2 can be connected.


Connection ZTH EU / Belimo Assistant 2



Dimensions

Spindle length


	Min. 40
	Min. 20 mm [0.75"]



Clamping range

			
	8...26.7	≥8	≤26.7
	8...20	≥8	≤20

*Option: Shaft clamp mounted below
(accessories K-NA needed)



Further documentation

- Overview MP Cooperation Partners
- Tool connections
- Introduction to MP-Bus Technology
- Quick Guide – Belimo Assistant 2

Application notes

- For digital control of actuators in VAV applications patent EP 3163399 must be considered.